



## LAVATORY FAUCET

- Two handle, metal lever, centerset lavatory faucet; model P299628LF plastic pop-up drain assembly, and model P299628LF-M with metal pop-up drain assembly.

## STANDARD SPECIFICATIONS:

- Maximum 1.2 gpm @ 60 psi, 4.5 L/min @ 414 kPa
- Three hole mount
- The fully replaceable, washerless valve design rotates from the full-off position to the full-on position in 90°
- The valve stems on the hot and cold stems are interchangeable
- 1/2"-14 NPSM threaded male inlet shanks
- RP76691 thick deck mounting kit adds 1 1/4" (32 mm) to maximum deck thickness

## WARRANTY

- Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes; or, for commercial users, for 5 years from date of purchase.
- 5 year limited warranty on electronic parts (other than batteries); or, for commercial users, for 1 year from the date of purchase. No warranty is provided on batteries.



## COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- ASME A112.18.2 / CSA B125.2
- Indicates compliance to ICC/ANSI A117.1
- EPA WaterSense®
- Verified compliant with 0.25% weighted average Pb content regulations.

▲ Designate proper finish suffix