

# CUBE ARCHITECTURAL DC-CD05

## LED Ceiling Mounts

# WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project: \_\_\_\_\_

Location: \_\_\_\_\_

### PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cubical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options.

### FEATURES

- Solid aluminum construction
- 39° visual cutoff angle for glare control
- 5 year warranty
- JA8-2016 Title 24 (Labeled with \*)

### SPECIFICATIONS

- Input:** Universal voltage 120V - 277VAC, 50/60Hz
- Dimming:** Electronic low voltage (ELV) : 100% - 5% (120V only)  
0-10V: 100% - 1% (120-277V)
- Light Source:** High output 3 Step Mac Adam Ellipse COB  
Rated life of 60,000 hours at L70
- Finish:** Electrostatically powder coated, white, black, bronze and graphite
- Standards:** IP65 rated, UL & cUL wet location listed

### ORDERING NUMBER

Diameter	Watt	Beam	Beam Angle	Color Temp	CRI	Lumens	CBCP	Efficacy (Lm/W)	Light Distribution	Finish
 <b>DC-CD05</b>	27W	<b>S</b> Spot	18°	<b>927*</b> 2700K	90	1680	8526	62		<b>BK</b> Black <b>WT</b> White <b>BZ</b> Bronze <b>GH</b> Graphite
				<b>827</b> 2700K	85	1800	9151	67		
				<b>930*</b> 3000K	90	1700	8639	63		
				<b>830</b> 3000K	85	1995	10126	74		
				<b>835</b> 3500K	85	2190	11118	81		
	<b>840</b> 4000K	85	2260	11483	84					
	27W	<b>N</b> Narrow	25°	<b>927*</b> 2700K	90	1730	5513	64		
				<b>827</b> 2700K	85	1855	5918	69		
				<b>930*</b> 3000K	90	1750	5587	65		
				<b>830</b> 3000K	85	2055	6548	76		
				<b>835</b> 3500K	85	2255	7190	84		
	<b>840</b> 4000K	85	2330	7426	86					
	27W	<b>F</b> Flood	33°	<b>927*</b> 2700K	90	1725	4246	64		
				<b>827</b> 2700K	85	1850	4557	69		
				<b>930*</b> 3000K	90	1745	4302	65		
<b>830</b> 3000K				85	2045	5043	73			
<b>835</b> 3500K				85	2245	5537	83			
<b>840</b> 4000K	85	2320	5719	86						

**DC-CD05-\_\_\_\_\_ - \_\_\_\_\_**

Example: **DC-CD05-N927-BK**

wacighting.com  
Phone (800) 526.2588  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050

Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91760

# CUBE ARCHITECTURAL DC-CD06

LED Ceiling Mounts

# WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project: \_\_\_\_\_

Location: \_\_\_\_\_

## PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cubical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options.

## FEATURES

- Solid aluminum construction
- 38° visual cutoff angle for glare control
- 5 year warranty
- JA8-2016 Title 24 (Labeled with \*)

## SPECIFICATIONS

- Input:** Universal voltage 120V - 277VAC, 50/60Hz
- Dimming:** Electronic low voltage (ELV) : 100% - 5% (120V only)  
0-10V: 100% - 1% (120-277V)
- Light Source:** High output 3 Step Mac Adam Ellipse COB  
Rated life of 70,000 hours at L70
- Finish:** Electrostatically powder coated, white, black, bronze and graphite
- Standards:** IP65 rated, UL & cUL wet location listed

## ORDERING NUMBER

Diameter	Watt	Beam	Beam Angle	Color Temp	CRI	Lumens	CBCP	Efficacy (Lm/W)	Light Distribution	Finish
<p><b>DC-CD06</b></p>	36W	<b>S</b> Spot	19°	<b>927*</b> 2700K 90 1875 8911 51	19°					
				<b>827</b> 2700K 85 2400 11392 65						
				<b>930*</b> 3000K 90 2000 9500 54						
				<b>830</b> 3000K 85 2170 10317 59						
				<b>835</b> 3500K 85 2500 11884 68						
		<b>840</b> 4000K 85 2450 11639 66								
		<b>N</b> Narrow	30°	<b>927*</b> 2700K 90 1830 4642 49	30°					
				<b>827</b> 2700K 85 2340 5935 63						
				<b>930*</b> 3000K 90 1950 4949 53						
				<b>830</b> 3000K 85 2120 5374 57						
				<b>835</b> 3500K 85 2440 6191 66						
		<b>840</b> 4000K 85 2390 6063 65								
		<b>F</b> Flood	40°	<b>927*</b> 2700K 90 1840 3310 50	40°					
				<b>827</b> 2700K 85 2355 4231 64						
				<b>930*</b> 3000K 90 1965 3528 53						
<b>830</b> 3000K 85 2130 3832 58										
<b>835</b> 3500K 85 2455 4414 66										
<b>840</b> 4000K 85 2405 4323 65										

- BK** Black
- WT** White
- BZ** Bronze
- GH** Graphite

**DC-CD06-\_\_\_\_\_ - \_\_\_\_\_**

Example: **DC-CD06-N927-BK**

waclighting.com  
Phone (800) 526.2588  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050

Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91760