

## **BASICS**

## 120V/24VDC 60W Electronics Transformer

| Model                    | Finish |
|--------------------------|--------|
| EN-BT60-24<br>EN-BT96-24 |        |

| Example: | EN-BT60-24 |
|----------|------------|
|----------|------------|

### **FEATURES**

- Input: 120 VAC, 50/60Hz
- 6" Output lead wires
- ELV Dimming (100-10%)
- Secondary wiring for Class 2 transformers does not require conduit sheathed cable or clamp wiring techniques
- $\bullet$  Intrinsically safe, Class 2 transformers permit no greater than a 5 amp current be drawn
- Non-metallic sheathed cable may be used for secondary wiring in walls and ceilings
- Built-in auto reset, soft start, short and overload circuit
- 5 Year warranty

#### **SPECIFICATIONS**

 Input:
 120 VAC, 50/60Hz

 Dimming:
 ELV: 100-10%

 Rated Life:
 50000 Hours

Mounting: Mounting metal case with screws, Can be mounted on

ceiling or wall in all orientations

Operating Temp:  $-4^{\circ}F$  to  $104^{\circ}F$  ( $-20^{\circ}C$  to  $40^{\circ}C$ )

Standards: UL, cUL, Damp Location Listed, IP20, ADA

Fixture Type:

Catalog Number:

Project:

Location:





# **BASICS**

120V/24VDC 60W Electronics Transformer

| Fixture Type:   |  |
|-----------------|--|
| Catalog Number: |  |
| Project:        |  |
| Location:       |  |

| ACCESSORIES |                   |             |        |  |  |
|-------------|-------------------|-------------|--------|--|--|
|             | Model             | Description | Finish |  |  |
|             | LED-T-B           | InvisiLED®  | White  |  |  |
|             | T24-BS-EX2-072-WT | BASICS      | WHITE  |  |  |
|             | T24-BS-IC-002-WT  | BASICS      | WHITE  |  |  |
|             | T24-BS-MM-CL      | BASICS      | CLEAR  |  |  |
| E G         | T24-BS-PM-CL      | BASICS      | CLEAR  |  |  |
|             | T24-BS-X-WT       | BASICS      | WHITE  |  |  |
|             | T24-BS-Y-WT       | BASICS      | WHITE  |  |  |